

ATHENA BM/W

WALL STANDING BAIN MARIE MODULE


Heated buffet with laminated wood structure and rear mirror to increase visual depth and provide the unit with a larger upper shelf. Capacity modules: 3-4-5-6 GN 1/1 according to model. Fid plexiglass® sneezeguard. Models with bainmarie heating. To avoid fogging of the lower part of the mirror in the BM version, we recommend the use of lids on the GN pans. Available too some units with halogen lamps for a dry top heating. LED lighting and two polyamide wheels with brakes as standard. GN pans not included.












MEASURE / CAPACITY

3 GN	4 GN	5 GN
------	------	------

PANELLING






FINISHES

						
OLM LOM	BIRCH LBE	VEINED WHITE LBV	WHITE SAND LWS	FOG LNE	WALNUT LNO	WENGÈ LWE
						
ANTHRACITE LAN	VEINED BLACK LNV	SILVER LAR	CAPPUCCI- NO LCP	GREY LGR	CLAY LTC	SAGE LSV
						
IVY LER	LIME LIM	NIAGARA LNI	OCEAN LOC	SKY LSK	ROSE LRS	SAFFRON LZA
						
COLOR TO SCIEGLERE IN THE FUTURE TO BE DEFINED						

OPTIONAL TRAY HOLDERS

					
6	7	8	3/FO	6/FO	9/FO
					
3-A	3-TUB	3-SST	9-A	9-STTA	9-TUBA
					
9C	9C-TUBC	9C-SSTC			

VARIOUS

					
5	PZH	ZH	UK	ADS	45CUT
					
GN	DIST	TEBT			

BODY



4



10



14

EXTENSION



17



17CH

TECHNICAL DATA

<i>Technical data</i>	ATHENA 3	ATHENA 4	ATHENA 5	ATHENA 6
GN Capacity	3	4	5	6
External dimensions (mm)	1174 x 747 x 1515	1499 x 747 x 1515	1824 x 747 x 1515	2149 x 747 x 1515
Net weight (Kg)*	123 BM 128 BM HALO 152 PC HALO	145 BM 148 BM HALO 175 PC HALO	167 BM 172 BM HALO 199 PC HALO	192 BM 197 BM HALO
Packaging size (cm)	135 x 92 x 185h	155 x 92 x 185h	185 x 92 x 185h	220 x 92 x 185h
Working temperature (°C)	0 / +90	0 / +90	0 / +90	0 / +90
power consumption(Watt)	2263 BM 1763 BM HALO - PC HALO	3016,5 BM 2393 BM HALO - PC HALO	3018 BM 3023 BM HALO - PC HALO	3250 BM 3250 + 1150 BM HALO
Supply voltage at 50 Hz (V)	230 V	230 V	230 V	230 V

* Model weight without options

TECHNICAL DRAWING

