



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- SB6 600 GRIDDLE SPLASHB
- SB7 750 GRIDDLE SPLASHB
- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The griddle has a chrome surface which both heats up quicker, and transfers heat to food more efficiently than standard griddles, with less energy loss as well as reduced energy radiation, which keeps the kitchen cooler for staff and reduces pressure on the ventilation system. Perfect for cafes, pubs and restaurants, the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results.

PRODUCT FEATURES

- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- Transfers heat to food more efficiently than a standard griddle
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK ELECTRIC COUNTER-TOP GRIDDLE - CHROME PLATE - SINGLE ZONE - W 600 MM - 3.0 KW

MODEL: GS6/C

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	600 mil
Height	330 mil
Weight	40.6 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	70 cm
Ship Height	63.5 cm
Ship Weight	44.66 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	Hardwired
Electrical Total Amperage	13 A	Number of Electrical Plugs	Not Applicable
Electrical Volts	230V	Number of Electrical Conductor Wires	1
Electrical Total Wattage	3000 W	Dedicated Circuit Required	Yes
Electrical Kilowatts	3 kW	Electrical Remarks	Single
Electrical Phase	1-Phase		

ADDITIONAL SPECIFICATIONS

Construction Materials	Stainless Steel	Number of Heating Zones	1
Control Type	Rotary Control Knob	Plate Thickness	12 mm
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	562 mm	Ventless Cooking Technology	No
Cooking Plate Finish Material Type	Chrome Plated	Temperature Maximum	250 °C
Lower Platen Surface Type	Smooth	Temperature Minimum	50 °C
Number Of Controls	1	Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

