



PANTHER

PRODUCT OPTIONS AND ACCESSORIES

- CP16 CP16 - CARVERY PAD [1/1 GASTRONORM SIZE]
- PGK6 GN PACK 6
- PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD
- PGK4 PGK4 - GASTRONORM PACK
- PGK5 PGK5 - GASTRONORM PACK
- PGK7 PGK7 - GASTRONORM PACK
- PHTC PHTC - CERAMIC INSERT [1/1 GASTRONORM SIZE]
- PHTG PHTG - GLASS INSERT [1/1 GASTRONORM SIZE]
- PPB6 PPB6 - ADDITIONAL PUSHBAR

PRODUCT FEATURES

- Ideal to fit through narrow corridors and doorways
- Bain marie top, ideal for small restaurants, cafes and pubs, as well as nursing and care homes, where the easy transportation of plated meals to diners and residents is a necessity
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 3 x 1/1 GN containers up to 150mm deep.
- Thermostatically controlled bain marie top can be operated with wet or dry heat. Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads
- Drain tap located inside the hot cupboard allows fast and easy draining

AIA FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	1205 mil
Depth	672 mil
Height	912 mil
Weight	95.6 kg

SHIPPING DETAILS

Ship Width	120 cm
Ship Depth	80 cm
Ship Height	103 cm
Ship Weight	105.16 kg
Number of Shipment Parcels	1
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	12.4 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	2850 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	2.85 kW	Dedicated Circuit Required	No
Electrical Phase	1-Phase	Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Cart Style	Plated Meals and Pans	Number of Shelves	2
Construction Materials	Stainless Steel	Plate Capacity	302
Control Type	Digital Touch Pad, Electronic	Plate Diameter	11.25" to 12.75"
Gastronorm Capacity	3 x GN1/1	Shelf Depth	512 mm
Heating System	Electric	Shelf Width	966 mm
Number of Doors	2	Temperature Maximum	99 °C
Number of Shelf Positions	4	Temperature Minimum	20 °C

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

