





B-series B HW-series



The taste of quality worldwide

BRAVILOR BONAMAT





Some situations ask for large quantities of coffee. This may affect the quality, unless you opt for a round filter machine from Bravilor Bonamat. This machine is ideal for peak moments, such as the interval in the theatre or the coffee supply in the hospital. Quickly and easily large quantities of coffee, brewed in convenient, moveable containers that enable you to serve coffee at any moment and at any place you want.

B (HW)-series: both quantity and quality

- Delicious, fresh filter coffee
- Stainless steel filter pan and housing for a robust and high-quality look
- Coffee-is-ready signal
- Option: cups, decanters, litres or gallons
- Total and day counters
- Descale system
- Integrated timer
- Adjustable brewing time for optimum extraction
- Maximum safety: container and swivel arm safety



B-series

If you need a large quantity of fresh filter coffee brewed in a relatively short time, the round filter machines of Bravilor Bonamat are the solution. The B-series includes four models with volumes of 5, 10, 20 and 40 litres. Within these volumes any required quantity of coffee can be easily made. The machines have very user-friendly programming and the design is really worth looking at too: the robust stainless steel look endorses the quality of the machine. A number of models are specially designed for marine use. The machines have a built-in timer, so you don't have to be present when the coffee is being brewed. The coffee will be ready when you get there!

Options B (HW)-series

- Various containers
- Trolleys
- Pedestal for smoothly placing vacuum containers below the tap
- Quick tap hose
- Swivel outlet
- Filter basket
- Micro filter: no need for filter paper
- Wall consoles for mounting the machine on the wall
- Tip-up plate for placing containers on the wall
- Tea filter and tea setting-up device







B HW-series

Do you also need hot water in addition to coffee? Then opt for the B HW-series. These machines have separate hot water taps for, for instance, very easily making tea. This series includes three types: 5, 10 and 20 litres. By default, the B (HW)-series consists of a column and two containers, but the machines are also available in single models with one container on the left or the right and a column. This allows for easy compilation of, for example, double or triple machines to make even larger quantities of coffee. There are several models that have been adapted to various situations. With these large machines safety is important. Built-in safety devices make sure that no coffee is brewed when there is no container below the outlet or when the outlet has not been placed above the container.

B (HW) W-series

Both series are also available in wall-mounted models, so you can make coffee at a central place and serve it locally. The containers are easily moveable using one of the trolleys from our product range. We also deliver a broad range of stackable containers: double-walled and with, among other things, a gauge glass and a non-drip tap. Also available with a double tap, as insulated model and as tea container.

Models containers					
Туре	Contents	Description			
VG	5, 10, 20 en 40 litres	Completely insulated			
VHG	5, 10, 20 en 40 litres	Electrical heating			
VHG T	5, 10, 20 en 40 litres	Electrical heating and thermostatically con- trolled. Especially for tea			
VHG D	5, 10, 20 en 40 litres	Electrical heating and extra non-drip tap			



The Bravilor Bonamat filter basket is extremely suitable for the use of filter cups, a good alternative to flat filter paper.

Container	Dimensions (hxø)
5 litres	445x210 mm
10 litres	464x286 mm
20 litres	510x374 mm
40 litres	629x423 mm

The taste of quality worldwide

BRAVILOR BONAMAT



Standard model (2 containers)	B5 (HW) (W)	B10 (HW) (W)	B20 (HW) (W)	B40 (W)
Coffee-making section				
Holding capacity	10 litres	20 litres	40 litres	80 litres
Throughput per hour	approx. 30 litres	approx. 60 litres	approx. 90 litres	approx. 145 litres
Brewing time (water flow)	approx. 10 min./5 litres	approx. 10 min./10 litres	approx. 14 min./20 litres	approx. 17 min./40 litres
Hot water section (HW)				
Holding capacity	3 litres	3,3 litres	4,6 litres	-
Throughput per hour	approx. 20 litres	approx. 20 litres	approx. 20 litres	-
Rated power B-series				
230V~ 50/60Hz	3130W	-	-	-
400V~ 3N 50/60Hz	3130W	6180W	9240W	15120W
Rated power B HW-series				
400V~ 3N 50/60Hz	5330W	8380W	11440W	-
Dimensions (wxdxh)				
Dimensions B-series	635x440x799 mm	955x512x840 mm	1173x600x947 mm	1305x652x1101 mm
Dimensions B HW-series	790x570x799 mm	989x570x840 mm	1173x600x947 mm	-
Dimensions B-series W	980x559x740 mm	1125x593x781 mm	1257x586x888 mm	1295x586x1042 mm
Dimensions B HW-series W	980x559x740 mm	1155x593x781 mm	1257x592x888 mm	-
Single model (1 container)	B5 (HW) (W) L/R	B10 (HW) (W) L/R	B20 (HW) (W) L/R	B40 (W) L/R
Single model (1 container) Coffee-making section	B5 (HW) (W) L/R	B10 (HW) (W) L/R	B20 (HW) (W) L/R	B40 (W) L/R
	B5 (HW) (W) L/R 5 litres	B10 (HW) (W) L/R 10 litres	B20 (HW) (W) L/R 20 litres	B40 (W) L/R 40 litres
Coffee-making section				
Coffee-making section Holding capacity	5 litres	10 litres	20 litres	40 litres
Coffee-making section Holding capacity Throughput per hour	5 litres approx. 30 litres	10 litres approx. 60 litres	20 litres approx. 90 litres	40 litres approx. 145 litres
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow)	5 litres approx. 30 litres	10 litres approx. 60 litres	20 litres approx. 90 litres	40 litres approx. 145 litres
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW)	5 litres approx. 30 litres approx. 10 min./5 litres	10 litres approx. 60 litres approx. 10 min./10 litres	20 litres approx. 90 litres approx. 14 min./20 litres	40 litres approx. 145 litres
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres	40 litres approx. 145 litres
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres	40 litres approx. 145 litres
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 400V~ 3N 50/60Hz	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres	40 litres approx. 145 litres
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 400V~ 3N 50/60Hz Rated power B HW-series	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres 3065W	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres approx. 20 litres	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres approx. 20 litres - 9120W	40 litres approx. 145 litres approx. 17 min./40 litres - -
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 400V~ 3N 50/60Hz Rated power B HW-series 400V~ 3N 50/60Hz	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres 3065W	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres approx. 20 litres	20 litres approx. 90 litres approx. 14 min/20 litres 4,6 litres approx. 20 litres	40 litres approx. 145 litres approx. 17 min./40 litres - -
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 400V~ 3N 50/60Hz Rated power B HW-series 400V~ 3N 50/60Hz	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres 3065W 3065W 5265W	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres approx. 20 litres - 6090W 8290W	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres approx. 20 litres - 9120W 11320W	40 litres approx. 145 litres approx. 17 min./40 litres - - - 14960W -
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 230V~ 3N 50/60Hz Rated power B HW-series 400V~ 3N 50/60Hz Dimensions (wxdxh) Dimensions B-series	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres 3065W 3065W 5265W	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres approx. 20 litres - 6090W 8290W 612x512x840 mm	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres approx. 20 litres - 9120W 11320W 739x600x947 mm	40 litres approx. 145 litres approx. 17 min./40 litres - -
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 400V~ 3N 50/60Hz Rated power B HW-series 400V~ 3N 50/60Hz Dimensions (wxdxh) Dimensions B-series Dimensions B HW-series	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres 3065W 3065W 5265W 452x440x799 mm 546x570x799 mm	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres approx. 20 litres 	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres approx. 20 litres 9120W 11320W 739x600x947 mm 739x600x947 mm	40 litres approx. 145 litres approx. 17 min./40 litres - - 14960W - 803x652x1101 mm
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 230V~ 3N 50/60Hz Rated power B HW-series 400V~ 3N 50/60Hz Dimensions (wxdxh) Dimensions B-series	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres 3065W 3065W 5265W	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres approx. 20 litres - 6090W 8290W 612x512x840 mm	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres approx. 20 litres - 9120W 11320W 739x600x947 mm	40 litres approx. 145 litres approx. 17 min./40 litres - - - 14960W -
Coffee-making section Holding capacity Throughput per hour Brewing time (water flow) Hot water section (HW) Holding capacity Throughput per hour Rated power B-series 230V~ 50/60Hz 230V~ 3N 50/60Hz Rated power B HW-series 400V~ 3N 50/60Hz Dimensions B-series Dimensions B-series	5 litres approx. 30 litres approx. 10 min./5 litres 3 litres approx. 20 litres 3065W 3065W 5265W 452x440x799 mm 546x570x799 mm	10 litres approx. 60 litres approx. 10 min./10 litres 3,3 litres approx. 20 litres 	20 litres approx. 90 litres approx. 14 min./20 litres 4,6 litres approx. 20 litres 9120W 11320W 739x600x947 mm 739x600x947 mm	40 litres approx. 145 litres approx. 17 min./40 litres - - 14960W - 803x652x1101 mm

Your Bravilor Bonamat dealer

We recommend:

- Bravilor Bonamat filter paper
- Renegite for descaling
- Cleaner for cleaning

www.bravilor.com

The taste of quality worldwide