



*Opus* **800**

#### PRODUCT OPTIONS AND ACCESSORIES

- LK02 OPUS 350 LEG KIT
- OA8954 SPLASHGUARD FOR OPUS 800 ELECTRIC FRYERS

#### PRODUCT FEATURES

- Two independent fryer tanks for greater versatility
- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Pumped oil return enables the oil to be filtered and the fryer ready for use again in less than five minutes - safe and convenient
- Oil can be filtered during or after service even whilst hot
- Hinged, lift out element, with safety interlock for easy tank access and cleaning

Fry delicious food accurately with this Opus 800 Twin-Tank Free Standing Electric Fryer which comes with two independent fryer tanks for greater versatility. The fryer boasts a pumped oil system which allows the oil to be filtered and ready to use again in less than five minutes. The two-stage filtration system not only extends oil life by up to 75%, but also saves you money. With a precise thermostatic control, the fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. The hinged, lift out element with safety interlock makes it easy to access and clean the tank.

AIA FILE NUMBER:

ITEM NUMBER:



# LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 600 MM - 24.0 KW

## MODEL: OE8113/OP

### WEIGHTS & DIMENSIONS

|        |          |
|--------|----------|
| Width  | 600 mil  |
| Depth  | 800 mil  |
| Height | 1070 mil |
| Weight | 104 kg   |

### SHIPPING DETAILS

|                            |                         |
|----------------------------|-------------------------|
| Ship Width                 | 70 cm                   |
| Ship Depth                 | 85 cm                   |
| Ship Height                | 122 cm                  |
| Ship Weight                | 114.4 kg                |
| Number of Shipment Parcels | 1                       |
| Ship Method                | LTL Common Carrier      |
| Shipping Package Type      | Pieces                  |
| Shipping Origin Zip Code   | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product         | No                      |

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

|                               |                                                       |
|-------------------------------|-------------------------------------------------------|
| Primary Energy Type           | Electric                                              |
| Electrical Amps Per Conductor | L1/L2/L3= 34.8 [1 cab];<br>L1/L2/L3= 2 x 17.4 [2 cab] |
| Electrical Total Amperage     | 34.8 A                                                |
| Electrical Volts              | 400V                                                  |
| Electrical Total Wattage      | 24000 W                                               |
| Electrical Kilowatts          | 24 kW                                                 |

|                                      |                  |
|--------------------------------------|------------------|
| Electrical Phase                     | 3-Phase          |
| Electrical Plug Type                 | Hardwired        |
| Number of Electrical Plugs           | Not Applicable   |
| Electrical Connection Type           | Direct Hardwired |
| Number of Electrical Conductor Wires | 1                |
| Dedicated Circuit Required           | Yes              |
| Electrical Remarks                   | Three            |



# LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 600 MM - 24.0 KW

## MODEL: OE8113/OP

### ADDITIONAL SPECIFICATIONS

|                                   |                                                                  |                             |            |
|-----------------------------------|------------------------------------------------------------------|-----------------------------|------------|
| Auto Oil Top-Off                  | No                                                               | Number of Baskets           | 2          |
| Basket Lift Type                  | Not Applicable                                                   | Number of Vats (batteries)  | 2          |
| Construction Materials            | Stainless Steel                                                  | Total Oil Capacity (volume) | 30 l       |
| Control Type                      | Mechanical                                                       | Oil Reclamation             | No         |
| Filter Media Type (if applicable) | 2-Stage: Fine Tissue Filter and Stainless Steel Filter           | Oil Temperature Control     | Mechanical |
|                                   |                                                                  | Pumped Oil Filtration       | Yes        |
|                                   |                                                                  | Vat 1 Oil Capacity (volume) | 15 l       |
| Food Production Rate              | 64kg chips - 12mm [frozen], 84kg chips - 12mm [chilled] per hour | Vat 2 Oil Capacity (volume) | 15 l       |
|                                   |                                                                  | Ventless Cooking Technology | No         |
| Fryer Type                        | Open Pot                                                         | Split Pot                   | Yes        |
| Integrated Filtration             | Yes                                                              | Temperature Maximum         | 190 °C     |

### BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

**TECHNICAL DRAWING**

