lincat

LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 14.0 KW

MODEL: OE8105/OP



Fry delicious food accurately with this Opus 800 Twin-Tank Free Standing Electric Fryer which comes with two independent fryer tanks for greater versatility. The fryer features a pumped oil system which allows the oil to be filtered and ready to use again in less than five minutes. The two-stage filtration system not only extends oil life by up to 75%, but also saves you money. Boasting a precise thermostatic control, the fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. The hinged, lift out element with safety interlock makes it easy to access and clean the tank.

)pus <mark>800</mark>

PRODUCT OPTIONS AND ACCESSORIES

- LK02 OPUS 350 LEG KIT
- OA8954 SPLASHGUARD FOR OPUS 800 ELECTRIC FRYERS

PRODUCT FEATURES

- Two independent fryer tanks for greater versatility
- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Pumped oil return enables the oil to be filtered and the fryer ready for use again in less than five minutes safe and convenient
- Oil can be filtered during or after service even whilst hot
- Hinged, lift out element, with safety interlock for easy tank access and cleaning





lincat

LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 14.0 KW

MODEL: 0E8105/0P

WEIGHTS & DIMENSIONS

Width	400 mil
Depth	800 mil
Height	1070 mil
Weight	84 kg

SHIPPING DETAILS	
Ship Width	85 cm
Ship Depth	45 cm
Ship Height	122 cm
Ship Weight	92.4 kg
Number of Shipment Parcels	1
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric
Electrical Amps Per Conductor	L1=20.3; L2=20.3; L3=20.3
Electrical Total Amperage	60.9 A
Electrical Volts	400V
Electrical Total Wattage	14000 W
Electrical Kilowatts	14 kW

3-Phase
Hardwired
Not Applicable
Direct Hardwired
1
Yes
Three

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

www.lincat.co.uk | p: +44 1522 875500

Document Auto-Generated January 09, 2025





LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 14.0 KW

MODEL: 0E8105/0P

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No
Basket Lift Type	Not Applicable
Construction Materials	Stainless Steel
Control Type	Mechanical
Filter Media Type (if applicable)	2-Stage: Fine Tissue Fil- ter and Stainless Steel Filter
Food Production Rate	40kg chips - 12mm [frozen], 56.2kg chips - 12mm [chilled] per hour
Fryer Type	Open Pot
Integrated Filtration	Yes

Number of Baskets	2
Number of Vats (batteries)	2
Total Oil Capacity (volume)	19 l
Oil Reclamation	No
Oil Temperature Control	Mechanical
Pumped Oil Filtration	Yes
Vat 1 Oil Capacity (volume)	9.5 l
Vat 2 Oil Capacity (volume)	9.5 l
Ventless Cooking Technology	No
Split Pot	Yes
Temperature Maximum	190 °C

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025





LINCAT OPUS ELECTRIC FREE-STANDING TWIN TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 400 MM - 14.0 KW

MODEL: 0E8105/0P

TECHNICAL DRAWING



Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 09, 2025